

# Mitigation of PEMFC Degradation upon Freeze-Thaw Cycling using a Methanol-Water Solution as Antifreeze

Florian Knorr, Daniel Garcia Sanchez, Johannes Schirmer, Pawel Gazdzicki,  
K. A. Friedrich

German Aerospace Center (DLR), Institute of Engineering Thermodynamics,  
70569 Stuttgart, Germany



Knowledge for Tomorrow





# Contents

- Introduction
- F/T cycling
- Start-up procedures involving antifreeze
- Conclusions



# Durability and Performance of PEMFC

- Durability and performance versus Pt loading including PGM-free electrodes
- Impact of Pt-loading on reversible and irreversible degradation and recovery of reversible losses
- Linking performance losses with local operation conditions, SoH monitoring
- **Investigate impact of stressors on durability and development of specific in-situ AST**
  - **Impact of F/T cycling on durability**
  - **Start up at  $T < 0^{\circ}\text{C}$**
  - **Mitigation of degradation due to F/T cycling**



# Freezing as stressor for PEMFC

## Freezing water in the cell cause damage to the MEA components

⇒ *Required to mitigate freezing*

- Getting rid of water before bringing cell to  $T < 0^{\circ}\text{C}$   
(→ purging cell by dry gas)
- Mitigate freezing of water when starting at  $T < 0^{\circ}\text{C}$   
(→ active heating, apply low voltage)

**Alternative:** flood cell by alcohol-water solution to avoid freezing



*Journal of The Electrochemical Society*, **151** (5) A661-A665 (2004)  
0013-4651/2004/151(5)/A661/5/\$7.00 © The Electrochemical Society, Inc.

### Effects of Water Removal on the Performance Degradation of PEMFCs Repetitively Brought to $<0^{\circ}\text{C}$


EunAe Cho,<sup>a</sup> Jae-Joon Ko,<sup>b,d</sup> Heung Yong Ha,<sup>a,\*</sup> Seong-Ahn Hong,<sup>a</sup>  
Kwan-Young Lee,<sup>b</sup> Tae-Won Lim,<sup>c</sup> and In-Hwan Oh<sup>a,z</sup>

<sup>a</sup>Fuel Cell Research Center, Korea Institute of Science and Technology, Seongbuk-ku, Seoul 136-791, Korea

<sup>b</sup>Department of Chemical and Biological Engineering, Korea University, Seongbuk-ku, Seoul 136-701, Korea

<sup>c</sup>Hyundai Motor Company, Fuel Cell Vehicle Team, Namyang-myun, Whasung-gun, Kyunggi-do 445-850, Korea

<http://www.novosolution.ca/images/Freezing-Points-Methanol.pdf>






# Experimental setup


## MEA

Parameter	Anode	Cathode
Active area	5 x 5 cm <sup>2</sup>	
Catalyst	Pt/C or PtRu/C	Pt/C
Pt loading	0.1 mg cm <sup>-2</sup>	0.25 mg cm <sup>-2</sup>
Membrane	PFSA, 10 micron	




## Test conditions

Parameter	Anode	Cathode
Cell temp. / °C	80	
Gases	H <sub>2</sub>	Air
RH	100%	100%
Stoich.	1.3	1.5
Pressure / bar <sub>a</sub>	2.5	2.3





Test bench for F/T cycling with MeOH as antifreeze

# F/T cycling and conditioning procedures





# F/T cycling tests (I)

No conditioning



# F/T cycling tests (II)



Dry gas purging







# F/T cycling tests (III)

## Antifreeze




# Sample analysis




# Start-up procedures involving antifreeze


DMFC mode



PEMFC mode with antifreeze




PEMFC mode without antifreeze



$T = -10^{\circ}\text{C}$




# Start-up in PEMFC mode without antifreeze



Rapid performance drop due to icing at  $T < 0^\circ\text{C}$



# Start-up in DMFC mode




Problem: **low anodic PtRu loading** and a **thin membrane** of used MEA do not allow to handle poor methanol oxidation kinetics and mitigate methanol cross over, respectively.





# Start-up in PEMFC mode with antifreeze




Successful cold start (< 30 s to 50% power) carried out in a stack by using a conventional start-up (drying with N<sub>2</sub> before freezing) shows initial current of **80–120 mA cm<sup>-2</sup>**

⚡ If successful cold start is possible using antifreeze, it is expected that residual methanol is removed due to evaporation at higher temperature and by drag with product water

# Conclusions

- Antifreeze strongly reduces performance degradation during F/T cycling: no degradation of peak performance
- Residual antifreeze allows continuous PEMFC operation at sub-zero temperatures
- Residual antifreeze reduces cell performance at  $T > 0^{\circ}\text{C}$

*Antifreeze will be tested in PEMFC stack as next step within INN-Balance Project*



Applied Energy

Volume 238, 15 March 2019, Pages 1-10



## Methanol as antifreeze agent for cold start of automotive polymer electrolyte membrane fuel cells

Florian Knorr <sup>a</sup>, Daniel Garcia Sanchez <sup>a</sup>, Johannes Schirmer <sup>a</sup>, Pawel Gazdzicki <sup>a</sup>, K.A. Friedrich <sup>a, b</sup>

[Show more](#)

<https://doi.org/10.1016/j.apenergy.2019.01.036>

[Get rights and content](#)



# Thank you for your attention

Contact: [pawel.gazdzicki@dlr.de](mailto:pawel.gazdzicki@dlr.de)

## Acknowledgements

This project has received funding from the Fuel Cells and Hydrogen 2 Joint Undertaking under grant agreement No research 735969 (**INN-Balance**). This Joint Undertaking receives support from the European Union's Horizon 2020 research and innovation programme, Hydrogen Europe and Hydrogen Europe research.

